AKIJ **BATHWARE** 🔤

Technical Data Sheet

CORDELIA SERIES



Part No: DWG-TDSM-4101 Chrome

Product Description:

- * KN-35 Ceramic mixing cartridges conventional single-lever type 35 mm sizes.
- * Brass ingots quality standard EN 1980.
- * CASS 4H/AASS 48 by standard procedure ASTM B117/ASTM B 368/09 JIS Z 2371/ISO.
- * Product specifications EN 817 for cartridges (Life endurance up to 70000 cycles).
- * Product Specifications ASME A112.18.1M for cartridges (Life endurance up to 500000 cycles.
- * Pressure Test For Cartridge Passed: 3bar/45psi-EN817.
- * Cartridge Flow Rate: 30.7 l/min / 8.1 gpm without resistance 20.7 l/min / 5.4 gpm with resistance "C"
- * Inlet Thread Size G3/4.

Plating:

- * Total plating thickness for Brass Faucet : 12.3 microns to 12.5 microns.
- * Semi bright and bright nickel: 12 microns.
- * Chrome: 0.3 to 0.5 microns.

This TDS supersedes those Issued previously.

Contents in this data sheet subject to change when required.

Please contact our nearest marketing executive/dealer for more details.

Code: CRD- 35011 Product: 3/4" 4 WAY TURN DIVERTER SHOWER MIXER (BRASS DISC)

